



TOUCHSCREEN DMX CONTROLLER

\$399.99

US MSRP

A standalone **5-inch touchscreen DMX512 controller** for moving heads, washes and pars. The whole show runs on the unit — **no laptop, no console, no software to install**. Build a look, save it to a scene, and fire it to the music.

BUILD THE LOOK

- **Movement:** Circle, Figure-8, Sweep, Wander — with speed, range and phase.
- **Color:** solid, alternate and chase; RGB plus white, amber, UV.
- **Beam:** strobe, gobo, prism, frost, zoom, focus, iris, lamp.
- **Groups A–D:** different looks on different lights at once.
- **8 instant scenes**, plus timed Auto Scene (5 s to 10 min).

PATCH & CONTROL

- **Up to 16 fixtures**, mixed rigs. 3 profiles built in (no Wi-Fi needed), hundreds more from the online Flow Library.
- **RDM** discovery and auto-patch (ANSI E1.20) for RDM-capable fixtures.
- **Phone and tablet control** over Wi-Fi — the full surface, live. No app.
- **USB MIDI** controllers and **OS2L** DJ-software sync (Virtual DJ and others).
- **Effects devices:** hold-to-fire or latching DMX-triggered foggers and hazers, with one KILL.
- **FlowLink** multi-unit sync — up to 8 followers. **Free over-the-air updates.**

**16**

FIXTURES

8

SCENES

4

GROUPS

4

PATTERNS

IN THE BOX

VFLOW controller

USB-C power adapter
USB-C to USB-C cable

Not included: DMX cable (3-pin XLR).
1-year limited warranty.

OPTIONAL ACCESSORY

**VBOX button box — \$39.99 MSRP**

An illuminated button that skips the touchscreen entirely. One press fires Blackout, Next Scene, Pattern, Fade, Effects or Hold Scene.

Includes a 3.3 ft (1 m) 1/4-inch TRS cable. Sold separately.

TECHNICAL SPECIFICATIONS

CONTROL & OUTPUT

DMX output
DMX512, 3-pin XLR

RDM
ANSI E1.20 controller

Fixtures
Up to 16, mixed rigs

Trigger input
1/4-inch TRS jack, 6 actions

DISPLAY & INTERFACE

Display
5" IPS touch, 1280×720

Wireless
Wi-Fi 6, browser control

USB
USB-A host for MIDI

DJ sync
OS2L over Wi-Fi

SOFTWARE

Profiles
3 built in; hundreds online

Custom profiles
On-device editor

Updates
Over the air, auto-rollback

Security
Optional PIN, 2 roles

SYSTEM & POWER

Processor
ESP32-P4 + ESP32-C6

Firmware
v1.4

Power
USB-C, adapter included

Warranty
1-year limited

Wi-Fi is needed for the online Flow Library, phone control and firmware updates; once patched, VFLOW runs the show on its own. Fixture profiles come from the open-source GDTF Share database (community-maintained) — verify fixture response before a live show. Specifications subject to change.